

Model	Σταθεροποιητής Τάσεως 230V	AVR-PL 600	AVR-PL 1000	AVR-PL 1500
Capacity		600VA/360W	1000VA/600W	1500VA/900W
AC Input	Normal Voltage	220/230/240VAC		
	Input Voltage Range	172VAC ~ 276VAC (-25%,+20%)		
	Phase	1 Phase 2 Wires		
	Frequency	50Hz or 60Hz		
AC Output	Output Voltage Range	207VAC ~ 252VAC (+/-10%)		
	Frequency	50Hz or 60Hz		
DC Output	Output Voltage Range	5VDC (+/-2%)		
Outlets	AVR/Surge only	4/2		
Protection	Network Surge Suppression	RJ-45/RJ-11		
	Overload	Manual Reset Circuit Switch		
	Short Circuit	Manual Reset Circuit Switch		
LED	Power On/Off	Green LED		
	Boost	orange LED		
	Buck	green LED		
Environment	Operating Temperature	0 ~ 40°C		
	Relative Humidity	0 ~ 95%, non-condensing		
	Audible Noise	< 40dB at 1M		
Physical	Dimension(D*W*H)	152*115*175mm		
	Net Weight	1.4Kgs	1.7Kgs	2.3Kgs
Design,Manufacture,Services		ISO 9001-2000		
Warranty		2 year		