

HEAT SHRINKAGE TUBES WITH GLUE GL TYPE



TECHNICAL SPECIFICATION

HEAT SHRINKAGE TUBES

Features:

- High quality, strength and resilience
- Adhesive lined polyolefin heat shrink, with a 3:1 shrinkage rate this tube shrinks to 1/3 of its diameter when heated. Appropriate for irregular shape insulation and sealing.
- Suitable for a wide range of applications, including electrical insulation, strain relief, cable bonding, color-coding and identification.
- The adhesive layer can be bonded to plastic, rubber and metal.
- Ease of use and durability, even in extreme conditions.



Variants:

Type	Colour	Diameter before shrinking (mm)	Wall thickness (mm)	Shrinkage ratio	Catalogue number
GL	black	D2.4 (≥ 2.4)	0.7 $\pm$ 0.15	3:1	3010024GL
GL	black	D3.2 (3.5 $\pm$ 0.3)	0.9 $\pm$ 0.15	3:1	3010032GL
GL	black	D4.8 (5.2 $\pm$ 0.3)	1.0 $\pm$ 0.15	3:1	3010048GL
GL	black	D6.4 (6.8 $\pm$ 0.4)	1.2 $\pm$ 0.15	3:1	3010064GL
GL	black	D7.9 (8.4 $\pm$ 0.4)	1.3 $\pm$ 0.15	3:1	3010079GL
GL	black	D9.5 (9.9 $\pm$ 0.4)	1.4 $\pm$ 0.15	3:1	3010095GL
GL	black	D12.7 (13.2 $\pm$ 0.5)	1.6 $\pm$ 0.20	3:1	3010127GL
GL	black	D15.0 (15.6 $\pm$ 0.5)	1.8 $\pm$ 0.20	3:1	3010150GL
GL	black	D19.1 (19.6 $\pm$ 0.5)	2.0 $\pm$ 0.20	3:1	3010191GL
GL	black	D25.4 (25.4 $\pm$ 0.8)	2.1 $\pm$ 0.20	3:1	3010254GL
GL	black	D30.0 (≥ 30)	2.2 $\pm$ 0.20	3:1	3010300GL
GL	black	D39 (≥ 40)	2.4 $\pm$ 0.20	3:1	3010390GL
GL	black	D50 (≥ 50)	2.7 $\pm$ 0.25	3:1	3010500GL
GL	black	D64 (≥ 60)	3.0 $\pm$ 0.25	3:1	3010640GL

TECHNICAL SPECIFICATION

HEAT SHRINKAGE TUBES

Packing:

Catalogue number	Barcode	Packing (pcs)
3010024GL	3800131222732	200
3010032GL	3800131222749	200
3010048GL	3800131222756	100
3010064GL	3800131222763	100
3010079GL	3800131222770	100
3010095GL	3800131222787	1,22
3010127GL	3800131222794	1,22
3010150GL	3800131222800	1,22
3010191GL	3800131222817	1,22
3010254GL	3800131222824	1,22
3010300GL	3800131222831	1,22
3010390GL	3800131222848	1,22
3010500GL	3800131222855	1,22
3010640GL	3800131222862	1,22

