

The Brand of Electricity

SINGLE- FUNCTION TIME RELAY, ELR-2B 1C-ON DELAY & 1C INSTANTANEOUS



Functions:

Single function time relays are suitable for applications where there is a clear function requirement in advance and are suitable for universal use in automation, control and regulation or in house installations. ELR-2B is easy for operation and has range of input voltage-from 24 till 240V AC/DC. Time setting is available from front panel.

TECHNICAL SPECIFICATION

AUTOMATION



Technical data:

• Voltage range: 24-240V; 50/60Hz

• Output current: 2x5A

• Function: 1C-On delay and 1C-Instantaneous


Output type: 2xSPDTTime ranges: 3s-10m

• Time setting: via 1 potentiometer

Time deviation: <±5%
 Repeat accuracy: <±5%
 Ingress protection: IP20
 Mechanical life: 1x10⁷
 Electrical life (AC1): 1x10⁵

• Max. cable size: solid wire max. 2.5 mm2 and

flexible wire 1.5 mm2
• Size: 90x18x64mm



Application:

- Control of electrical appliances
- Control of lights, heating, motors, pump, fan etc.

Variants:

Catalogue	Type	Dimensions (mm)			Packing/Box
number		W	Н	D	(pcs)
50152	ELR-2B	18	90	64	1/100

