

The Brand of Electricity

MULTI- FUNCTION TIME RELAY, ELR-4



Functions:

Multi-function time relays are suitable for applications where there is need more additional functions requirement and are suitable for universal use in automation, control and regulation or in house installations. ELR-4 is easy for operation and has range of input voltage - up 12 to 240V AC/DC. This relay increases 10 functions: 5 time functions controlled by supply voltage, 4 functions controlled by control input and 1 function of latching relay.

TECHNICAL SPECIFICATION

AUTOMATION



Technical data:

• Voltage range: 12-240V 50/60Hz

• Output current: 2x16A

• Function: 10

• Output type: 2xSPDT

• Time ranges: 0.1s-240h ON/OFF


• Function setting: via 3 potentiometers on front panel

Time deviation: 10% mechanical setting
Repeat accuracy: 0.2% set value stability

• Min. breaking capacity DC: 500mW

Reset time: max. 200ms
 Over voltage category: III
 Output indication: red LED
 Ingress protection: IP20
 Mechanical life: 1x10⁷
 Electrical life (AC1): 1x10⁵

• Max. cable size: solid wire max. 2.5 mm2 and flexible wire 1.5 mm2



TIME RANGE





















Application:

- Control of industrial and home electrical appliances.
- Control of lights, heating, motors, pump, fan and etc.

Variants:

Catalogue	Type	Dimensions (mm) Packing/			
number		W	Н	D	Box (pcs)
50155	ELR-4	18	90	64	1/100

